

Endian Hotspot 150

Accesso Internet rapido e sicuro



Un prodotto dall'utilizzo intuitivo, dedicato ad offrire accesso Internet stabile e veloce, semplice da usare e facile da mantenere. Endian Hotspot 150 è la risposta alle esigenze di piccole aziende, esercizi commerciali e strutture ricettive che vogliono garantire l'utilizzo della rete Internet ai propri collaboratori e clienti, evitando il rischio di saturazione della banda o il pericolo di abusi da parte degli utenti.

Gestione semplificata degli utenti

Endian Hotspot offre due funzionalità importanti per semplificare l'accesso al web. Con SmartConnect l'utente riceve automaticamente le credenziali di accesso ad Internet, senza che l'operatore debba fare nulla. Con Social Login può autenticarsi direttamente tramite profilo Facebook o Google.

Piattaforma marketing integrata

L'Hotspot di Endian non è solo un servizio per i tuoi clienti, ma uno strumento per promuovere la tua attività. Il portale di accesso a Internet è totalmente personalizzabile: metti in evidenza le offerte speciali e le promozioni in corso. Mostra ai tuoi visitatori tutta la qualità dei tuoi servizi.

Con SmartLogin l'Hotspot si ricorda di te

Una funzionalità utile per tutti i tuoi clienti. Quando la navigazione viene interrotta e poi ripresa, l'Hotspot riconosce automaticamente l'utente senza chiedere di nuovo le credenziali di accesso.

Perfetto per il settore hospitality

Endian Hotspot 150 è l'appliance ideale per le strutture ricettive: garantisce ai clienti accesso veloce e semplice ad Internet, semplifica la gestione del servizio e offre infinite possibilità di personalizzazione del portale di ingresso, che si trasforma in una interessante piattaforma di promozione della struttura.

Endian Hotspot 150	
Utenti concurrenti	fino a 150
Throughput	250 Mbit/s
Ideale per	Hospitality, sale riunioni, sale di coworking, ristorazione, biblioteche, negozi e catene, uffici e filiali



Connessione WiFi
sicura



Piattaforma
marketing



Social Login

Endian Hotspot Features

Hotspot

User Management
<ul style="list-style-type: none"> Authentication through <ul style="list-style-type: none"> Local or external RADIUS LDAP / Active Directory Google / Facebook MAC-address accounts User accounts import/export User password recovery Social Login (Facebook / Google) User auto-creation through e-mail or SMS (SmartConnect) Bandwidth limitation per user Configurable multiple logins per user
Configuration and Integration
<ul style="list-style-type: none"> Multi-location setup through master/slave configuration Configurable captive portal Customizable templates WYSIWYG editor with multimedia file upload Multi-language support Configurable access to allowed sites (walled garden) Configurable mandatory Terms of Service confirmation Bandwidth limiting based on user, ticket or global settings JSON API for external accounting and third party integration Integration with property management systems ASA HOTEL, pcs phoenix
Accounting and Ticketing
<ul style="list-style-type: none"> Integrated RADIUS service Integrated accounting based on tickets Payment service through credit card and PayPal Freely configurable ticket rates Pre-/postpaid and free tickets Time-/traffic-based tickets Cyclic/recurring tickets (daily, weekly, monthly, yearly) Single-click ticket generation (Quick ticket) Configurable ticket and account validity MAC address tracking for free hotspots Remember user after first authentication (SmartLogin)

Networking

Uplink Management
<ul style="list-style-type: none"> Multiple WAN uplink support Multiple public IP addresses Automatic WAN uplink failover Monitoring of WAN uplinks Uplink types: Ethernet (static/ DHCP), PPPoE, PPTP Support for 3G / 4G USB dongles
Networking Features
<ul style="list-style-type: none"> Separated network zones Quality of service and bandwidth management VLAN support Stealth mode OSI layer 2 firewall functionality Spanning tree Automatic client network configuration (DHCP / static IPs) Wired and wireless connections in the hotspot are supported NTP (Network Time Protocol) DHCP server Dynamic DNS
Network Address Translation (NAT)
<ul style="list-style-type: none"> Destination NAT Incoming routed traffic One-to-one NAT Source NAT (SNAT)
Routing
<ul style="list-style-type: none"> Static routing Source-based routing Destination-based routing Policy-based routing

Security

Threat Protection
<ul style="list-style-type: none"> Stateful packet firewall Application control SYN/ICMP flood protection DNS proxy/routing Anti-spyware Phishing protection Transparent HTTP/HTTPS web filtering Cyren URL filter with 140 million categorized URLs SafeSearch enforcement Time based access control with multiple time intervals Anti-virus
VPN
<ul style="list-style-type: none"> OpenVPN Native VPN client app for Microsoft Windows and Apple OS X Support for mobile devices (Android, iOS) Support for VPN over HTTP Proxy VPN client-to-site (roadwarrior) VPN failover VPN user and group management
Encryption
<ul style="list-style-type: none"> SSL-encrypted captive portal SSL-encrypted administration interface SSL-encrypted VPN connections between master and satellite systems Encrypted backups via email

Management Interface

Logging and Reporting
<ul style="list-style-type: none"> Reporting dashboard Detailed system, web and virus reports Hotspot connection logging Live network traffic monitoring (powered by ntopng) Live log viewer Detailed web access report Network/system/performance statistics Rule-based logging settings (firewall rules) Syslog: local or remote OpenTSA trusted timestamping Email Notifications SMS Notifications
Administration
<ul style="list-style-type: none"> Centralized management through Endian Network Easy web-based administration Multi-language web-interface Secure remote SSH/SCP access Serial console Centralized updates through Endian Network Scheduled automatic backups Instant recovery / Backup to USB stick (Endian Recovery Key) Different user roles for administrator, hotspot administrator and hotspot account editor

Endian Hotspot 150 Specifications

Hardware	Hotspot 150
Case	Desktop
Dimensions	44mm x 232mm x 153mm
Weight	1.1 kg
Memory	1 GB
Storage	1x 320 GB HDD
Networking	4x Gigabit Ethernet
LAN Bypass	-
Power Supply	40W External
Cooling	Fans
LCD Display	-
Hardware Warranty	included in maintenance
Certifications	FCC/CE/RoHS