

Reference Data

Eaton 5SC 750i

| Product | Short Description |
|------------------|--|
| Eaton 5SC 750i | Protection for tower server, networking and storage, LCD display, 750 VA / 525 W, Line-Interactive with AVR & sinewave output, USB and Serial port + contacts, shutdown software, 6 IEC outlets, replaceable batteries, compact design |
| EATON Ref | |
| 5SC750i | |

| Packaging | Size (H x W x D*mm) | Weight (kg) | Number of Units / Packaging | UPC Code |
|----------------------|---------------------|-------------|-----------------------------|--------------|
| Individual packaging | 308 x 238 x 476 | 11.5 kg | 1 product / carton | 743172045157 |
| Complete pallet | 1065 x 1000 x 1200 | 365 kg | 30 cartons / pallet | |

| Packaging content |
|--|
| 1 UPS + 2 IEC output power cords + Eaton Intelligent Power Software CD + USB Cable + Serial Cable + Safety guide + Quick Start + CD with 10-language user manual |

| Technical Specifications | |
|----------------------------|---|
| Technology | Line interactive HF, Sinewave output |
| Capacity | 750 VA / 525 W |
| Size (H x W x D*)/Weight | 210 x 150 x 340 mm / 10.4 kg |
| Output Receptacles | 6 IEC 10A |
| Output Voltage / Frequency | 230 V (adjustable to 220-230-240V) / 50-60 Hz autosensing |
| Input Voltage tolerance | 184V-276V |
| Features | Automatic Voltage Regulation via Booster&Fader, Advanced battery monitoring (ABM), Deep discharge protection, Automatic battery test, Replace battery indicator, Cold start, adjustable sensitivity to disturbed networks |
| Administration | 1 USB port + 1 serial RS232 & contacts port |
| User interface | LCD : access to measures, alarms, status |
| Warranty | 2 years |
| Standards | IEC/EN 62040-1 (Safety), IEC/EN 62040-2 class B (EMC), CE, CB report |
| Quality | Designed, manufactured and marketed under ISO9001 & ISO14001 quality system |

| Load (%) | 5 | 8 | 10 | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 |
|-------------------|-----|-----|----|----|----|------|------|----|----|----|----|-----|
| Runtime (minutes) | 124 | 100 | 74 | 38 | 23 | 16,5 | 12,5 | 11 | 9 | 7 | 6 | 5 |

| Selling points |
|--|
| <ul style="list-style-type: none"> Reliable and affordable UPS for tower servers, networking, and storage Easy to operate : LCD display Automatic voltage regulation and sinewave output Compact design for easy integration Monitoring & shutdown software for Windows, Linux, ... 1 USB port & 1 Serial + contact port for compatibility with existing or future hardware Advanced Battery Management (ABM) technology to increase battery lifetime Replaceable batteries from front panel |

| Options | Reference |
|------------|-----------|
| Warranty + | 66812 |
| Warranty 5 | W5001 |

*H x W x D= Height x Width x Depth