



**STORMSHIELD** 

## Stormshield SN200

NETWORK SECURITY I ENDPOINT SECURITY I DATA SECURITY

## Stormshield SN2000

THE SECURITY SOLUTION IDEAL FOR BUSINESSES & LARGE ORGANIZATIONS REQUIRING HIGH PERFORMANCE AND FLEXIBILITY.



#### DON'T CHOOSE BETWEEN PERFORMANCE AND SECURITY

With throughput that can reach 30 Gbps, look no further for better value and performance in a network protection appliance.



## TAKE ADVANTAGE OF THROUGHPUT FROM NEW-GENERATION NETWORKS

The SN2000's 10GB fiber network connectivity and unrivalled modularity make it easy to integrate naturally into new-generation networks to meet or anticipate your needs.



#### UP THE BANDWIDTH OF YOUR NETWORK LINKS

Thanks to their physical link aggregation feature (LACP), Stormshield Network Security appliances ensure greater availability than ever in your infrastructure. By merging several physical interfaces in order to create a single link, you will be able to leverage the bandwidth allocated to this link.



## RESTRICT INAPPROPRIATE USE WITH APPLICATION CONTROL

The application control function on Stormshield Network Security appliances makes it possible to curb the use of dangerous applications or those unrelated to work. It is based on a qualitative approach that favors the integration of applications that are truly relevant to corporations and their core business.



## BUSINESSES & LARGE ORGANIZATIONS

## Ensure the continuity of your business

All protection technologies needed for responding to the most sophisticated attacks are embedded in the entire range.

#### Manage vulnerabilities

Obsolete or vulnerable applications on workstations and servers are detected in real time.

## Keep your commitments to compliance

Stormshield Network Security products are a key component in ensuring compliance with standards, regulations and norms that require access control (PCI-DSS, ISO 27001 or the Data Protection Act, etc.).

## Stay in control of your internet usage

Thanks to advanced filtering and the management of quality of service, you can define the way you want the internet to be used.

.....

# Technical specifications

#### USAGE CONTROL

Firewall/IPS/IDS mode, identity-based firewall, application firewall, Microsoft Services Firewall, detection and control of the use of mobile terminals, application inventory (option), vulnerability detection (option), filtering per localisation (countries, continents), URL filtering (embedded database or cloud mode), transparent authentication (Active Directory SSO Agent, SSL, SPNEGO), multi-user authentication in cookie mode (Citrix- TSE), guest mode authentication, time scheduling per rule.

#### PROTECTION FROM THREATS

Intrusion prevention, protocol scan, application inspection, protection from denial of service attacks [DoS], protection from SQL injections, protection from Cross-Site Scripting [XSS], protection from malicious Web2.0 code and scripts, Trojan detection, detection of interactive connections (botnets, Command&Control), protection from data evasion, Advanced management of fragmentation, automatic quarantining in the event of an attack, Antispam and antiphishing: reputation-based analysis —heuristic engine, embedded antivirus [HTTP, SMTP, POP3, FTP], detection of unknown malware via sandboxing, SSL decryption and inspection, VoIP protection [SIP], collaborative security: Dynamic Host Reputation, IP reputation.

#### CONFIDENTIALITY

Site-to-site or nomad IPSec VPN, remote SSL VPN access in multi-OS tunnel mode (Windows, Android, iOS, etc), SSL VPN agent configurable centrally (Windows), Support for Android/iPhone IPSec VPN.

#### **NETWORK - INTEGRATION**

IPv6, NAT, PAT, transparent (bridge)/routed/hybrid modes, dynamic routing (RIP, OSPF, BGP), multi-level internal or external PKI management, multi-domain authentication (including internal LDAP), explicit proxy, policy-based routing (PBR), QoS management, DHCP client/relay/server, NTP client, DNS proxycache, HTTP proxy-cache, high availability, WAN link redundancy, LACP management, Spanning-tree management (RSTP/MSTP), IPFIX/NetFlow.

#### MANAGEMENT

Web-based management interface, object-oriented security policy, real-time configuration help, firewall rule counter, more than 15 installation wizards, global/local security policy, embedded log reporting and analysis tools, interactive and customizable reports, sending to syslog server UDP/TCP/TLS, SNMP v1, v2, v3 agent, automated configuration backup.

**Non-contractual document.** The features mentioned are those in version 3.0.

<sup>\*\*</sup> IP size: 60% (48 bytes) – 25% (494 bytes) – 15% (1500 bytes).

| PERFORMANCE*                                                                            |                              |
|-----------------------------------------------------------------------------------------|------------------------------|
| Firewall throughput (1518 byte UDP)                                                     | 30 Gbps                      |
| Firewall (IMIX**)                                                                       | 11 Gbps                      |
| IPS throughput (1518 byte UDP)                                                          | 20 Gbps                      |
| IPS throughput (1 Mbyte HTTP files)                                                     | 12 Gbps                      |
| Antivirus throughput                                                                    | 3.2 Gbps                     |
| VPN*                                                                                    |                              |
| IPSec throughput - AES128/SHA1                                                          | 5 Gbps                       |
| IPSec throughput - AES256/SHA2                                                          | 4 Gbps                       |
| Max number of IPSec VPN tunnels                                                         | 5,000                        |
| Number of SSL VPN clients (Portal mode)                                                 | 1,024                        |
| Number of simultaneous SSL VPN clients                                                  | 200                          |
| NETWORK CONNECTIVITY                                                                    |                              |
| Concurrent connections                                                                  | 2,000,000                    |
| New sessions per second                                                                 | 90,000                       |
| Number of main gateways (max)/backup (max)                                              | 64/64                        |
| Number of interfaces [Agg, Dialup, ethernet, loopback, VLAN, pptp,]                     | 1,300                        |
| CONNECTIVITY                                                                            |                              |
| 10/100/1000 interfaces                                                                  | 10-26                        |
| 1Gb fiber interfaces                                                                    | 0-16                         |
| 10Gb fiber interfaces                                                                   | 0-8                          |
| Optional interfaces<br>(8 ports 10/100/1000 - 4 or 8 ports 1Gb SFP - 4 ports 10Gb SFP+) | 2                            |
| SYSTEM                                                                                  |                              |
| Max number of filtering rules                                                           | 32,768                       |
| Max number of static routes                                                             | 10,240                       |
| Max number of dynamic routes                                                            | 10,000                       |
| REDUNDANCY                                                                              |                              |
| High Availability (Active/Passive)                                                      | <b>~</b>                     |
| HARDWARE                                                                                |                              |
| Local storage                                                                           | 128 GB SSD                   |
| Racking                                                                                 | 1U - 19"                     |
| Height x Width x Depth (mm)                                                             | 44.5 x 443 x 560             |
| Weight                                                                                  | 8.6 kg (19 lbs)              |
| Packaged Height x Width x Depth (mm)                                                    | 184 x 710 x 573              |
| Packaged weight                                                                         | 15.6 kg (34.4 lbs)           |
| Power supply (AC)                                                                       | 110-230V 60-50Hz 3.5-1.5A    |
| Power consumption                                                                       | 230V 50Hz 174W 0.95A         |
| Fan                                                                                     | 3                            |
| Operational temperature                                                                 | 5° to 40°C (41° to 104°F)    |
| Relative humidity, operating (without                                                   | 20% += 00% @ 40°C            |
| condensation)                                                                           | 20% to 90% @ 40°C            |
| Storage temperature                                                                     | -30° to 65°C (-22° to 149°F) |
| Relative humidity, storage (without condensation)                                       | 5% to 95% @ 60°C             |
| CERTIFICATIONS                                                                          |                              |
| Compliance                                                                              | CE/FCC                       |
|                                                                                         |                              |

<sup>\*</sup> Performance is measured in a laboratory and under conditions ideal for version 3.0. Results may vary according to test conditions and the software version.

## For security with high added value



### STORMSHIELD NETWORK VULNERABILITY MANAGER\*

Arm yourself with a simple and powerful vulnerability detection tool that leaves no impact on your information system.

#### **Vulnerability Management**

Based on data passing through the appliance, Stormshield Network Vulnerability Manager makes an inventory of operating systems, applications used and their vulnerabilities. As soon as a vulnerability appears on your network, you will be kept informed.

#### Remediation

Stormshield Network Vulnerability Manager offers a set of dedicated reports as well as a real-time dashboard that allow you to stay in control of your deployment.



### STORMSHIELD NETWORK EXTENDED WEB CONTROL\*

Monitor how users surf the internet on your corporate network and optimize your bandwidth consumption by deploying an effective and high-performance URL filtering solution.

#### Prevention of web-based threats

Extended Web Control analyzes illions of requests in order to continuously evaluate the risk level of various websites and to block infected or malicious sites from being visited as soon as they are detected.

#### Advanced filtering for all

The Extended Web Control solution can be enabled on the entire range of Stormshield Network Security products. You can therefore benefit from an advanced filter solution regardless of the size of your company.



#### KASPERSKY ANTIVIRUS\*

Protect yourself by getting equipped with the best antivirus protection solution.

#### **Protection from threats**

The Kaspersky antivirus solution on Stormshield Network Security appliances is not based merely on a system of malware signatures, but also integrates emulation mechanisms to identify malicious code proactively.

#### Peripheral protection

Applying an antivirus inspection on the traffic of all devices connected to the network and relying on a behavioral analysis technology similar to sandboxing, it allows the detection of even unknown attacks.

\* Option



Phone +33 9 69 32 96 29

WWW.STORMSHIELD.EU