



**BUSINESS CONTINUITY IN COMPLEX ARCHITECTURES** 

## Stormshield SN910

NETWORK SECURITY I ENDPOINT SECURITY I DATA SECURITY

## Stormshield SN910

THE SECURITY SOLUTION DEDICATED TO MIDSIZED ORGANIZATIONS AND LARGE AGENCIES REQUIRING HIGH-SPEED FIBER CONNECTIVITY (10GB).



#### PERFORMANCE AND MODULARITY

Offering 20 Gbps performance, the SN910 is able to adapt to your needs thanks to network modularity that combines port density (up to 16 ports) with 10GE fiber.



## AUTOMATICALLY IDENTIFY APPLICATIONS ON THE NETWORK

Application control, installed on all Stormshield Network Security appliances, allows you to automatically identify applications used (local or web applications) by your coworkers thanks to a dynamic analysis of the contents of connections.



#### KEEP YOUR COMMITMENTS TO COMPLIANCE

Stormshield Network Security solutions are a key component in keeping your commitments with regard to standards or regulations such as PCI-DSS, HIPAA, ISO270X as well as complying with legislation on data protection.



#### KEEP TRACK OF MOBILE TERMINALS

With the identification of mobile terminals logged on to the information system, the use of such devices can be allowed or blocked during certain time slots, for certain users or groups to certain resources, or a stronger protection profile can even be applied.



## IMPROVE THE SECURITY POLICY ACCORDING TO CONTEXT

Adapt the level of protection for a workstation or server according to the level of risk identified (security alarms generated or vulnerabilities detected). In security reports, select your risk mitigation strategy in just one click.



#### MID-SIZE BUSINESSES AND LARGE AGENCIES

## Ensure the continuity of your business

All protection technologies needed for responding to the most sophisticated attacks are embedded in the entire range.

## Stay in control of your internet usage

Thanks to advanced filtering and the management of quality of service, you can define the way you want the Internet to be used.

#### Manage vulnerabilities

Obsolete or vulnerable applications on workstations and servers are detected in real time.

#### Save time

The administration interface on Stormshield Network Security products has been designed to be ergonomic and intuitive in order to assist you in securing your corporate network quickly and with zero errors.

:....:

# Technical specifications

#### **USAGE CONTROL**

Firewall/IPS/IDS mode, identity-based firewall, application firewall, Microsoft Services Firewall, detection and control of the use of mobile terminals, application inventory (option), vulnerability detection (option), filtering per localisation (countries, continents), URL filtering (embedded database or cloud mode), transparent authentication (Active Directory SSO Agent, SSL, SPNEGO), multi-user authentication in cookie mode (Citrix-TSE), guest mode authentication, time scheduling per rule.

#### PROTECTION FROM THREATS

Intrusion prevention, protocol scan, application inspection, protection from denial of service attacks [DoS], protection from SQL injections, protection from Cross-Site Scripting [XSS], protection from malicious Web2.0 code and scripts, Trojan detection, detection of interactive connections (botnets, Command&Control), protection from data evasion, Advanced management of fragmentation, automatic quarantining in the event of an attack, Antispam and antiphishing: reputation-based analysis —heuristic engine, embedded antivirus [HTTP, SMTP, POP3, FTP], detection of unknown malware via sandboxing, SSL decryption and inspection, VoIP protection [SIP], collaborative security: Dynamic Host Reputation, IP reputation.

#### CONFIDENTIALITY

Site-to-site or nomad IPSec VPN, remote SSL VPN access in multi-OS tunnel mode (Windows, Android, iOS, etc), SSL VPN agent configurable centrally (Windows), Support for Android/iPhone IPSec VPN.

#### **NETWORK - INTEGRATION**

IPv6, NAT, PAT, transparent (bridge)/routed/hybrid modes, dynamic routing (RIP, OSPF, BGP), multi-level internal or external PKI management, multi-domain authentication (including internal LDAP), explicit proxy, policy-based routing (PBR), QoS management, DHCP client/relay/server, NTP client, DNS proxycache, HTTP proxy-cache, high availability, WAN link redundancy, LACP management, Spanning-tree management (RSTP/MSTP), IPFIX/NetFlow.

#### MANAGEMENT

Web-based management interface, object-oriented security policy, real-time configuration help, firewall rule counter, more than 15 installation wizards, global/local security policy, embedded log reporting and analysis tools, interactive and customizable reports, sending to syslog server UDP/TCP/TLS, SNMP v1, v2, v3 agent, automated configuration bvvackup.

**Non-contractual document.** The features mentioned are those in version 3.0.

•••••

PERFORMANCE*           Firewall throughput (1518 byte UDP)         20 6bps           IPS throughput (1518 byte UDP)         12.5 6bps           IPS throughput (1 Mbyte HTTP files)         7 6bps           Antivirus throughput         2.2 6bps           VPN*         ***           IPSec throughput - AES128/SHA1         4 6bps           IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         **           Concurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           106 b fiber interfaces         0-5           107/100/1000 interfaces         3-2,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         **
IPS throughput (1 Mbyte HTTP files)         7 Gbps           Antivirus throughput         2.2 Gbps           Antivirus throughput         2.2 Gbps           VPN*         1PSec throughput - AES128/SHA1         4 Gbps           IPSec throughput - AES256/SHA2         3 Gbps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           Concurrent connections         1,500,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8.16           106 fiber interfaces         0-6           106b fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of dynamic routes         10,000           REDUNDANCY         Itigh Availability (Active/Passive)         ✓           HARDWARE         Local storage         1206B SSD           MTBF (years)         13,2           Racking         1U - 19°
IPS throughput (1 Mbyte HTTP files)         7 6bps           Antivirus throughput         2.2 6bps           VPN*         PSec throughput - AES128/SHA1         4 6bps           IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         TSO           Concurrent connections         1,500,000           Number of main gateways [max]/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           106 fiber interfaces         0-6           106b fiber interfaces         0-6           106b fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         Italy           High Availability (Active/Passive)         ✓           HARDWARE         Local storage         1206B SSD           MTBF (years)
VPN*           VPN*           IPSec throughput - AES128/SHA1         4 6bps           IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           1Gb fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         Wigh Availability (Active/Passive)         ✓           HARDWARE         Local storage         1206B SSD           MTBF (years)         13,2           Racking         10-19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight
VPN*           IPSec throughput - AES128/SHA1         4 6bps           IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           1Gb fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of dynamic routes         10,000           REDUNDANCY         Wigh Availability (Active/Passive)         ✓           HARDWARE         Local storage         1206B SSD           MTBF (years)         13,2           Racking         10-19°           Height x Width x Depth (mm)         44,45x x 440 x 310           Weight         5.1 kg (11.31bs)
IPSec throughput - AES128/SHA1         4 6bps           IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         Toncurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           1Gb fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         ✓           High Availability (Active/Passive)         ✓           HARDWARE         Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19"           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5,1 kg (11,31 lbs)
IPSec throughput - AES256/SHA2         3 6bps           Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           16b fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         ↓           High Availability (Active/Passive)         ↓           HARDWARE         Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5,1 kg (11,31 lbs)
Max number of IPSec VPN tunnels         1,000           Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         Toncurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           1Gb fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         ▼           High Availability (Active/Passive)         ▼           HARDWARE         Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
Number of SSL VPN clients (Portal mode)         300           Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           16b fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of dynamic routes         10,000           REDUNDANCY         Itigh Availability (Active/Passive)         ✓           HARDWARE         Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
Number of simultaneous SSL VPN clients         150           NETWORK CONNECTIVITY         1,500,000           Concurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           16b fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         Igh Availability (Active/Passive)         ✓           HARDWARE         Jocal storage         1206B SSD           MTBF (years)         13,2           Racking         1U-19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
NETWORK CONNECTIVITY           Concurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           1Gb fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of static routes         5,120           Max number of dynamic routes         10,000           REDUNDANCY         ★           High Availability (Active/Passive)         ★           HARDWARE         Local storage         120GB SSD           MTBF (years)         13,2           Racking         10-19"           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
Concurrent connections         1,500,000           New connections per second         60,000           Number of main gateways (max)/backup (max)         64/64           Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)         750           CONNECTIVITY         10/100/1000 interfaces         8-16           16b fiber interfaces         0-6           10Gb fiber interfaces         0-2           SYSTEM         32,768           Max number of filtering rules         32,768           Max number of dynamic routes         10,000           REDUNDANCY         ★           High Availability (Active/Passive)         ★           HARDWARE         Local storage         1206B SSD           MTBF (years)         13,2           Racking         10-19°           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
New connections per second60,000Number of main gateways (max)/backup (max)64/64Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)750CONNECTIVITY8-1610/100/1000 interfaces8-16106b fiber interfaces0-610Gb fiber interfaces0-2SYSTEMMax number of filtering rules32,768Max number of static routes5,120Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)✓HARDWARELocal storage1206B SSDMTBF (years)13,2Racking10 - 19"Height x Width x Depth (mm)44.45 x 440 x 310Weight5.1 kg (11.3 lbs)
Number of main gateways (max)/backup (max)64/64Number of interfaces (Agg, Dialup, ethernet, loopback, VLAN, pptp,)750CONNECTIVITY10/100/1000 interfaces8-1616b fiber interfaces0-610Gb fiber interfaces0-2SYSTEMMax number of filtering rules32,768Max number of static routes5,120Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)✓HARDWARELocal storage120GB SSDMTBF (years)13,2Racking1U - 19"Height x Width x Depth (mm)44.45 x 440 x 310Weight5.1 kg (11.3 lbs)
Number of interfaces [Agg, Dialup, ethernet, loopback, VLAN, pptp,]  CONNECTIVITY  10/100/1000 interfaces 8-16  16b fiber interfaces 0-6  106b fiber interfaces 0-2  SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY High Availability (Active/Passive)   HARDWARE  Local storage 120GB SSD  MTBF (years) 13,2  Racking 10 - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
[Agg, Dialup, ethernet, loopback, VLAN, pptp,]  CONNECTIVITY  10/100/1000 interfaces 8.16  16b fiber interfaces 0-6  106b fiber interfaces 0-2  SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY  High Availability (Active/Passive) ✓  HARDWARE  Local storage 1206B SSD  MTBF (years) 13,2  Racking 10 - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
CONNECTIVITY  10/100/1000 interfaces 8-16  16b fiber interfaces 0-6  106b fiber interfaces 0-2  SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY  High Availability (Active/Passive) ✓  HARDWARE  Local storage 120GB SSD  MTBF (years) 13,2  Racking 1U - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
10/100/1000 interfaces       8-16         16b fiber interfaces       0-6         10Gb fiber interfaces       0-2         SYSTEM         Max number of filtering rules       32,768         Max number of static routes       5,120         Max number of dynamic routes       10,000         REDUNDANCY         High Availability (Active/Passive)       ✓         HARDWARE         Local storage       1206B SSD         MTBF (years)       13,2         Racking       10 - 19"         Height x Width x Depth (mm)       44.45 x 440 x 310         Weight       5.1 kg (11.3 lbs)
16b fiber interfaces 0-6 106b fiber interfaces 0-2  SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY  High Availability (Active/Passive) ✓  HARDWARE  Local storage 1206B SSD  MTBF (years) 13,2  Racking 1U - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY High Availability (Active/Passive) ✓  HARDWARE  Local storage 120GB SSD  MTBF (years) 13,2  Racking 1U - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
SYSTEM  Max number of filtering rules 32,768  Max number of static routes 5,120  Max number of dynamic routes 10,000  REDUNDANCY  High Availability (Active/Passive) ✓  HARDWARE  Local storage 120GB SSD  MTBF (years) 13,2  Racking 1U - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
Max number of filtering rules32,768Max number of static routes5,120Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)✓HARDWARELocal storage120GB SSDMTBF (years)13,2Racking10 - 19"Height x Width x Depth (mm)44.45 x 440 x 310Weight5.1 kg (11.3 lbs)
Max number of static routes5,120Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)✓HARDWARELocal storage120GB SSDMTBF (years)13,2Racking10 - 19"Height x Width x Depth (mm)44.45 x 440 x 310Weight5.1 kg (11.3 lbs)
Max number of dynamic routes10,000REDUNDANCYHigh Availability (Active/Passive)✓HARDWARE120GB SSDLocal storage120GB SSDMTBF (years)13,2Racking1U - 19"Height x Width x Depth (mm)44.45 x 440 x 310Weight5.1 kg (11.3 lbs)
REDUNDANCY High Availability (Active/Passive)  HARDWARE  Local storage 1206B SSD  MTBF (years) 13,2  Racking 1U - 19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
High Availability (Active/Passive)  HARDWARE  Local storage 120GB SSD  MTBF (years) 13,2  Racking 1U-19"  Height x Width x Depth (mm) 44.45 x 440 x 310  Weight 5.1 kg (11.3 lbs)
HARDWARE           Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19"           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
Local storage         120GB SSD           MTBF (years)         13,2           Racking         1U - 19"           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
MTBF (years)       13,2         Racking       1U - 19"         Height x Width x Depth (mm)       44.45 x 440 x 310         Weight       5.1 kg (11.3 lbs)
Racking         1U - 19"           Height x Width x Depth (mm)         44.45 x 440 x 310           Weight         5.1 kg (11.3 lbs)
Height x Width x Depth (mm)       44.45 x 440 x 310         Weight       5.1 kg (11.3 lbs)
Height x Width x Depth (mm)       44.45 x 440 x 310         Weight       5.1 kg (11.3 lbs)
· · · · · · · · · · · · · · · · · · ·
Packaged weight 7.05 kg (15.6 lbs)
Power supply (AC) 110-240V 60-50Hz 4-2A
Power consumption 230V 50Hz 72W 0.38A
Fan 3
Noise level 50dbA
Thermal dissipation (max, BTU/h) 334
Operational temperature 5° to 40°C (41° to 104°F)
Relative humidity, operating (without condensation) 20% to 90% @ 40°C
Storage temperature -30° to 65°C (-22° to 149°F)
Relative humidity, storage (without condensation) 5% to 95% @ 60°C
CERTIFICATIONS
Compliance CE/FCC

<sup>\*</sup> Performance is measured in a laboratory and under conditions ideal for version 3.0. Results may vary according to test conditions and the software version.

# For security with high added value



### STORMSHIELD NETWORK VULNERABILITY MANAGER\*

Arm yourself with a simple and powerful vulnerability detection tool that leaves no impact on your information system.

#### **Vulnerability Management**

Based on data passing through the appliance, Stormshield Network Vulnerability Manager makes an inventory of operating systems, applications used and their vulnerabilities. As soon as a vulnerability appears on your network, you will be kept informed.

#### Remediation

Stormshield Network Vulnerability Manager offers a set of dedicated reports as well as a real-time dashboard that allow you to stay in control of your deployment.



### STORMSHIELD NETWORK EXTENDED WEB CONTROL\*

Monitor how users surf the internet on your corporate network and optimize your bandwidth consumption by deploying an effective and high-performance URL filtering solution.

#### Prevention of web-based threats

Extended Web Control analyzes illions of requests in order to continuously evaluate the risk level of various websites and to block infected or malicious sites from being visited as soon as they are detected.

#### Advanced filtering for all

The Extended Web Control solution can be enabled on the entire range of Stormshield Network Security products. You can therefore benefit from an advanced filter solution regardless of the size of your company.



#### KASPERSKY ANTIVIRUS\*

Protect yourself by getting equipped with the best antivirus protection solution.

#### **Protection from threats**

The Kaspersky antivirus solution on Stormshield Network Security appliances is not based merely on a system of malware signatures, but also integrates emulation mechanisms to identify malicious code proactively.

#### Peripheral protection

Applying an antivirus inspection on the traffic of all devices connected to the network and relying on a behavioral analysis technology similar to sandboxing, it allows the detection of even unknown attacks.

\* Option



Phone +33 9 69 32 96 29

WWW.STORMSHIELD.EU